



OEC

Optical Engineer Companion

Metrology solution
The all-rounder

Metrology on-the-go
Modular system
Upgradable



OEC compatible



imagine
optic

OPTICAL ENGINEER COMPANION +

Our family of products now team up to support your optical metrology



Compatible with the Optical Engineer Companion modular system: easily combine the accessories you need.

CONFIGURATION

The OEC refers to a family of standard sensors and accessories that can be instantaneously combined to create the configuration you need for your optical tests.

Select the modules among:

a variety of metrology sources from UV to SWIR

1 a large range of HASO™ or LIFT wavefront sensors

2 several R-FLEX™ illumination systems

3 a choice of R-FLEX LA™ beam expanders

...and use them in combination or separately.

1

METROLOGY SOURCE: MS



MS- λ
400 - 1550 nm

Perfect waveform metrology source:

- + Monomode fiber
- + Manual or computer control
- + Adjustable intensity
- + Trigger input
- + Optical power: 5 mW

Reference	Wavelength (nm)
MS-405	405
MS-488	488
MS-520	520
MS-635	635
MS-785	785
MS-830	830
MS-1064	1064
MS-1550	1550
MS-CUSTOM	contact us for specific wavelength

2

WAVEFRONT SENSOR: HASO™ & LIFT



HASO LIFT 680
680 x 504 phase points



HASO LIFT 272
272 x 200 phase points



HASO4 126
350 - 1100 nm



HASO4 BROADBAND
350 - 1100 nm



HASO4 FIRST
 $\lambda/100$ RMS at custom wavelength



HASO4 FAST
1.25 kHz



HASO SWIR LIFT
160 x 128 phase points



HASO SWIR
0.9 - 1.7 μ m

ILLUMINATION SYSTEM: R-FLEX™



R-FLEX2 VIS
400 - 1100 nm



R-FLEX2 SWIR
1 - 1.7 μm

R-FLEX VIS and SWIR are illumination systems coupling our sources with our wavefront sensors for testing:

- + in double pass optical configuration
- + concave surfaces or refractive optics of any f/# choosing the appropriate focusing module (MOD F) below:

Compact, lightweight, insensitive to vibrations and atmospheric turbulences, R-FLEX is easy to align onto the optics to be tested.

It is the perfect solution for large telescopes, optics in vacuum chambers.

Reference	Focal length (mm)	Back power required (%)	Working distance ¹ (mm)	Module length ² (mm)	HASO LIFT 680 f/#, (wfe ³) (nm RMS)	HASO LIFT 272 f/#, (wfe ³) (nm RMS)	HASO4 126 / BROADBAND f/#, (wfe ³) (nm RMS)	HASO4 BROADBAND f/#, (wfe ³) (nm RMS)	HASO4 FIRST f/#, (wfe ³) (nm RMS)	HASO4 FAST f/#, (wfe ³) (nm RMS)	HASO SWIR LIFT f/#, (wfe ³) (nm RMS)	HASO SWIR f/#, (wfe ³) (nm RMS)
MOD F4.5	4.5	50	0.6	205.9	-	0.9 (120)	-	0.9 (120)	1.3 (30)	3.8 (5)	-	-
MOD F9	8.9	50	1.2	250.0	-	1.8 (40)	-	1.8 (40)	2.5 (10)	7.5 (5)	-	-
MOD F9 HR	9	50	0.6	247.8	0.9 (130)	-	0.9 (130)	-	-	-	-	-
MOD F18 HR	17.8	50	1.2	247.2	1.8 (50)	-	1.8 (50)	-	-	-	-	-
MOD F20	20.4	3	10.4	50.3	-	4 (160)	-	4 (160)	5.6 (40)	17.2 (5)	-	-
MOD F20 SWIR	20	3	10	71.8	-	-	-	-	-	-	2.7 (250)	2.7 (250)
MOD F31	30.3	3	-0.7	66.6	3 (250)	5.9 (20)	3 (250)	5.9 (20)	8.4 (10)	25.5 (5)	-	-
MOD F31 SWIR	31	3	10	114.7	-	-	-	-	-	-	4.2 (150)	4.2 (150)
MOD F40	41.7	3	8	40.8	4.1 (150)	8.1 (15)	4.1 (150)	8.1 (15)	11.5 (10)	35.1 (5)	-	-
MOD F40 SWIR	40	3	3.3	62.2	-	-	-	-	-	-	5.4 (100)	5.4 (100)
MOD F50	51.7	3	3.6	103.1	5.1 (100)	10 (10)	5.1 (100)	10 (10)	14.2 (5)	43.5 (5)	-	-
MOD F50 SWIR	50	3	3.3	92.1	-	-	-	-	-	-	6.8 (25)	6.8 (25)
MOD F60	60.1	3	15.2	42.5	5.9 (30)	11.7 (8)	5.9 (30)	11.7 (8)	16.5 (5)	50.5 (5)	-	-
MOD F60 SWIR	60	3	12.8	45	-	-	-	-	-	-	8.1 (50)	8.1 (50)
MOD F75	75.1	3	12.8	73.6	7.4 (20)	14.6 (5)	7.4 (20)	14.6 (5)	20.6 (5)	63.1 (5)	-	-
MOD F76 SWIR	75.3	3	12.8	74.3	-	-	-	-	-	-	10.2 (25)	10.2 (25)
MOD CUSTOM	contact us for specific aperture, working distance, etc.											

All focusing modules have pupil imaging: the microlens array of the wavefront sensor is imaged at the infinity by the focusing modules

¹Distance between the focal plane and the first mechanical interface of the module (with centering tool removed)

²Distance from the mounting interface of the module to the first mechanical interface of the module (with centering tool removed)

³Wavefront Error (wfe) at the output of the module for a circular pupil corresponding to the nominal f-number (f/#)

BEAM EXPANDER: R-FLEX LA™



R-FLEX LA VIS 100
100 mm test beam



R-FLEX LA SWIR 150
150 mm test beam

R-FLEX LA VIS and SWIR are beam expander coupling our R-FLEX for testing:

- + in double pass optical configuration
- + flat wavefront or surfaces of any diameter choosing the appropriate platform reference below:


Reference	Test diameter (mm)	Spectral range
LA.30	30	VIS, SWIR
LA.75	75	VIS, SWIR
LA.100	100	VIS, SWIR
LA.150	145	VIS, SWIR
LA.200	200	SWIR
LA.CUSTOM	contact us for specific diameter	

At wavelength, easy alignment and characterization of


beam expanders
filters, dichroic beamsplitter
flat mirrors
optical windows
polarization scramblers.

OPTICAL SETUPS


Concave surfaces / refractive optics testing: use R-FLEX™




(Uncoated) Small to large concave mirrors




Beam expanders
characterization and alignment




Beam expanders, afocal systems
characterization and alignment




(Very) Large telescopes and collimators
characterization and alignment




Filters, windows in transmission




Collimated lasers and external sources




Lenses of any diameter, on-axis



Mirrors, filters in reflection



Lenses of any diameter, in the field



Head-Up displays, dichroics, beam splitters



CONTACT US

Imagine Optic Headquarters
18, rue Charles de Gaulle
91400 ORSAY · France
Phone +33 (0)1 64 86 15 60
sales@imagine-optic.com
www.imagine-optic.com

imagine
optic