

HASO EUV

Wavefront sensor **The Hartmann**

From EUV to soft X-Ray
Achromatic technology
Vacuum compatible



Imagine Optic's HASO EUV wavefront sensor was developed in collaboration with LOA laboratory and the SOLEIL synchrotron.

It is the only device of its kind that offers you the extreme precision and direct measurement functionality needed for today's most demanding laboratory and industrial applications.

APPLICATIONS

Designed and built in collaboration with our customers to meet their needs, the HASO EUV performs multiple functions.

With it you can :

- + Align and characterize Synchrotron, EUV-FEL and laser-driven secondary source
- + Do micro- and nano-focusing
- + Diagnose dense plasma
- + Align automatically EUV optical systems
- + Make EUV lithography
- + Analyze gas or solid high-harmonic generation

FEATURES

- + Compatible with coherent and non-coherent sources
- + Usable for closed- and open-loop adaptive optics
- + Patented rotated square technology offering high resolution and wide dynamic range
- + Suitable for mono- and polychromatic beams
- + Hydrocarbon free and compatible with 10^{-7} mbar



SPECIFICATIONS*

OPERATING SPECS

Aperture dimension
Number of sub-apertures dedicated for analysis
Minimum readout time
Working photon energy (Wavelength range)
Operating system

Standard EUV

13 x 13 mm²
72 x 72
~ 600 ms (2MHz digitalization)
30-300 eV (4-40 nm)
Windows 10

High NA EUV

13.6 x 13.6 mm²
80 x 80
64 μ s to 2 s
25-250 eV (5-50 nm)
Windows 10

OPTICAL SPECS

Repeatability
Wavefront measurement accuracy
• In absolute mode
• In relative mode
Spatial sampling
Tilt measurement sensitivity
Focus dynamic range
Numerical aperture

~ $\lambda/200$ RMS

~ $\lambda/50$ RMS @ 13.5 nm
~ $\lambda/100$ RMS @ 13.5 nm
~ 180 μ m
0.05 μ rad RMS
 ± 0.5 m to $\pm \infty$
0.013

~ $\lambda/200$ RMS

< $\lambda/20$ RMS @ 10 nm
< $\lambda/40$
~ 170 μ m
0.1 μ rad RMS
 ± 0.45 m to $\pm \infty$
0.15


MISC

Dimensions (Height x Width x Length)
Weight
Sensor type
Working temperature
Compliant vacuum (hydrocarbon free)
Interface
Power consumption



\varnothing 115 mm, L 270 mm
8 Kg
Vacuum interface
15-30 °C
10⁻⁷ mbar
USB 2.0
12 VDC

276 x 102 x 114 mm³
3.3 Kg
In vacuum
15-30 °C
5x10⁻⁷ mbar
USB 3.0
60 W @ 12 VDC

*Subject to changes without further notice



DIMENSIONS (mm)



SOFTWARE


WAVEVIEW™ Metrology Software

WAVEVIEW™ is the most advanced wavefront measurement and analysis software.

It offers more than 150 features and tools optimized for a wide range of highly demanding applications.

Options :

- + Extensions for PSF, MTF, M² and Strehl ratio
- + Optional SDK in C, LabVIEW and Python



CONTACT US

Imagine Optic Headquarters
18, rue Charles de Gaulle
91400 ORSAY · France
Phone +33 (0)1 64 86 15 60
sales@imagine-optic.com
www.imagine-optic.com

